



## Home Plate Installation Procedures

Spread MAR-CO SPORT SAND evenly over sub grade to a compacted depth of 5", within 4" of the finished grade.

Install the MAR-CO HOME PLATE using compacted MAR-CO MOUND CLAY over the sport sand to level and elevate the home plate 1" above the home plate radius edge.

Spread MAR-CO MOUND CLAY in the batters and catchers boxes evenly over the sport sand to a compacted depth of 1". Dampen the area with water to assist the bonding of the MOUND CLAY and MAR-CO FIELD BRICKS.

Install MAR-CO FIELD BRICKS in a tightly laid pattern as shown on Top View. Spread a thin layer of MAR-CO MOUND CLAY over the bricks to fill any cracks and tamp firmly.

Spread MAR-CO HOME BASE BLEND inside the home plate radius, grade from edge of batters boxes to the grass edge.

Compact the home plate area and continue to spread and grade HOME BASE BLEND until the required elevations are achieved.



www.marcoclay.com

### MAR-CO CLAY PRODUCTS INC.

Bright, Ontario, CANADA  
ph : 519-684-7591

Distributed by :

### SAVARIA LANDSCAPE PRODUCTS INC.

Boucherville, Québec, CANADA  
ph : 1-877-728-2742 www.savaria.ca

Project Title

**HOME PLATE INSTALLATION**

### MAR-CO CLAY USA INC.

Wampum, PA USA  
ph : 866-344-9362

Date

**revised Feb 2010**

Consultant

Sheet #

**BBH2**