



Pitchers Mound Installation Procedures

Install MAR-CO PITCHING RUBBER using compacted MAR-CO MOUND CLAY over sub soil to level and elevate the pitching rubber 10" above the home plate elevation.

Spread MAR-CO MOUND CLAY and compact in the plateau and landing area to the required elevation. Dampen the area with water to assist the bonding of the MOUND CLAY and the MAR-CO FIELD BRICKS.

Install the MAR-CO FIELD BRICKS in a tightly laid pattern as shown on Top View. Spread a thin layer of MAR-CO MOUND CLAY over the bricks to fill any cracks and tamp firmly.

Spread MAR-CO MOUND CLAY inside the pitching mound radius, grade slopes as shown in Side View.

Compact the pitchers mound and continue to spread and grade MOUND CLAY until the required elevations are achieved.

Soak heavily and tarp to cure.



www.marcoclay.com

MAR-CO CLAY PRODUCTS INC.

Bright, Ontario, CANADA
ph : 519-684-7591

Distributed by :
SAVARIA LANDSCAPE PRODUCTS INC.

Boucherville, Québec, CANADA
ph : 1-877-728-2742 www.savaria.ca

Project Title

PITCHERS MOUND INSTALLATION

MAR-CO CLAY USA INC.

Wampum, PA USA
ph : 866-344-9362

Date

revised Feb 2010

Consultant

Sheet #

BBP2